


ADVS 4X4X4 (4+4) TECHNICAL SPECIFICATIONS







ADVS COMPLETE VEHICLE SYSTEM




Caterpillar C9 In-line 6 Diesel - 335.6 Kw (450 hp)

- 1849 N•m (1364 lb.-ft) Torque



ADVS 4x4x4 (4+4) TECHNICAL SPECIFICATIONS



Engine

Max Seating Capacity	8 Standard (10 optional)
Weight Curb Weight	15,900 kg (35,053 lbs)*
Maximum Gross Weight *Dependent or	23,000 kg (50,706 lbs) • Ballistic Level
Vehicle Dimensions	See Drawings Above
Ground Clearance min/max (at "V")	0.32 to 0.70 m (12.6 to 27.8 in)
Max Speed	100.0 kph (62.14 mph)* *Dependent on Tire Type
Fuel Capacity	530.0 liters (140 gal.)
Estimated Range (highway)	965.6 km (600 mi)
Fording Amphibious	1.98 m (78 in.) Dependent on Ballistic Level
Gradient	60%
Side Slope	30% (50% Optional)
Vertical Obstacle	0.46 m (18.0 in)
Trench Crossing 90° to Trench 45° to Trench	0.85 m (2 ft. 9.5 in.) 1.05 m (3 ft. 5.3 in.)
Turning Radius	7.8 m (25.6 ft.) All Wheel Steer
Central Tire Inflation (CTI)	Available
Run-flats	Available

	- 447.4 Kw (600 hp) - 1900 N•m (1401 lbft) Torque
Transmission	Caterpillar CX28 - Electronically Controlled - 6 Forward / 1 Reverse Gear
Suspension	400.0 mm (15.75 in.) Wheel Travel Ride-Height Adjustable (Optional)
Tires	395/85 R20 or 16.00 R20
Brakes Service Parking	Air w/ ABS Integral To Driveline
Electrical System	Distributed Bus System -12 V and 24 V
Vision	Large Periscopes, Thermal and Optical Cameras (Optional)
Hydraulic Winch	Available up to 133 kN (30,000 lbs)
Auxiliary Power Unit (APU)	Optional, for Power Generation (Internal and External Power)
Heating System	11 kW/h (37,600 btu/h)
Air Conditioning System	16.7 kW/h (57,000 btu/h)
Turret System	Can Mount Weapons from 7.62 mm Thru 30 mm Cannons
NBC System	Over-Pressure (Optional)

Subject To Change without Notice

ADVS COMPLETE VEHICLE SYSTEM

